

# FARO® Focus Laser Scanner

The Most Compact Lightweight and Intuitive Laser Scanner Product Line

## Laser Scanners for Short, Medium and Long Range Applications

FARO Focus Laser Scanners are specifically designed for both indoor and outdoor measurements in industries such as Architecture, Engineering, Construction, Public Safety and Forensics or Product Design. All devices capture real world information used in the digital world to analyze, collaborate and execute decisions to improve and maintain the overall project and product quality.

The Focus<sup>S</sup> Laser Scanner series offers advanced functionality. In addition to increased distance, angular accuracy, and range, the Focus<sup>S</sup> and Focus<sup>S</sup> Plus scanners' on-site compensation function ensures high-quality measurements, while external accessory bays and HDR functionality make the scanner extremely flexible.



## Features

### Accuracy

Highest accuracy and range by using a combination of the most advanced sensor technologies.

### Rescanning of Distant Targets

The Scan Group feature identifies multiple areas to be rescanned with higher resolution to either perform accurate target detection or to capture smaller areas of interest with greater detail.

### IP Rating 54 and Extended Temperature Range

With the sealed design and certified with the industry standard Ingress Protection (IP) Rating, IP54, the Focus can be used in wet weather conditions at temperatures from -20°C to 55°C<sup>8</sup>.

### Compact and Portable

Focus Laser Scanners are the smallest and lightest devices in their performance class.

### On-Site Compensation

With the on-site compensation functionality, users can verify and adjust the Focus<sup>S</sup> compensation immediately before scanning, ensuring high-quality scan data and traceable documentation.

### On-Site Registration

During on-site data capture, the laser scanner immediately transmits scan data wirelessly to FARO SCENE for real-time scan processing and registration, providing efficiency and time savings.

## Benefits

- Confidence in documented data-quality by traceable calibration and market-leading on-site compensation.
- Scan in challenging environments while providing protection from dust, debris and water splashes. Mount the Focus<sup>S</sup> scanner in an inverted position, such as under a ceiling of a hall.
- The Focus Laser Scanner portfolio offers the most economic 3D scanning solution for all requirements and budgets.
- Minimum training effort is ensured by the intuitive and easy to operate touch-screen interface as well as hands-on and online tutorials.
- Efficient integration into existing software infrastructures and workflows are provided by interfaces to various standard CAD systems.

Focus<sup>S</sup> and Focus<sup>S</sup> Plus

# Performance Specifications

|                                       | Focus <sup>s</sup> 350 Plus  | Focus <sup>s</sup> 150 Plus | Focus <sup>s</sup> 350                                  | Focus <sup>s</sup> 150 | Focus <sup>s</sup> 70 | Focus <sup>M</sup> 70          |
|---------------------------------------|--|-----------------------------|---|------------------------|-----------------------|--------------------------------|
| Ranging Unit                          |  |                             |   |                        |                       |                                |
| Unambiguity Interval                  | 614m for up to 0.5 mil pts/sec<br>307m at 1 mil pts/sec<br>153m at 2 mil pts/sec |                             | 614m for up to 0.5 mil pts/sec<br>307m at 1 mil pts/sec |                        |                       | 614m for up to 0.5 mil pts/sec |
| Range <sup>1</sup>                    |  |                             |   |                        |                       |                                |
| 90% Reflectivity (white)              | 0.6-350m   | 0.6-150m                    | 0.6-350m  | 0.6-150m               | 0.6-70m               | 0.6-70m                        |
| 10% Reflectivity (dark-gray)          | 0.6-150m   | 0.6-150m                    | 0.6-150m  | 0.6-150m               | 0.6-70m               | 0.6-70m                        |
| 2% Reflectivity (black)               | 0.6-50m  | 0.6-50m                     | 0.6-50m   | 0.6-50m                | 0.6-50m               | 0.6-50m                        |
| Range Noise <sup>2</sup> (mm)         |  |                             |   |                        |                       |                                |
| @10m 90% (white)                      | 0.1  |                             | 0.3   |                        |                       | 0.7                            |
| @10m 10% (dark-gray)                  | 0.3  |                             | 0.4   |                        |                       | 0.8                            |
| @10m 2% (black)                       | 0.9  |                             | 1.3   |                        |                       | 1.5                            |
| @25m 90% (white)                      | 0.2  |                             | 0.3   |                        |                       | 0.7                            |
| @25m 10% (dark-gray)                  | 0.5  |                             | 0.5   |                        |                       | 0.8                            |
| @25m 2% (black)                       | 1.6  |                             | 2.0   |                        |                       | 2.1                            |
| Max. Measurement Speed (mil. pts/sec) | Up to 2  |                             | Up to 1   |                        |                       | Up to 0.5                      |
| Ranging Error <sup>3</sup> (mm)       | ±1   |                             |   |                        |                       | ±3                             |
| Angular Accuracy <sup>4</sup>         | 19 arcsec for vertical/horizontal angles   |                             |   |                        |                       | not specified                  |
| 3D Point Accuracy <sup>5</sup>        | 2 @10m 3.5 @25m  |                             | 2 @10m 3.5 @25m   |                        |                       | not specified                  |

| Additional Performance Specifications |  |
|---------------------------------------|--|
| Color Unit                            |  |
| Color Resolution                      | Up to 165-megapixel color  |
| HDR Camera                            | Exposure bracketing 2x, 3x, 5x   |
| Parallax                              | Minimized due to co-axial design   |
| Deflection Unit                       |  |
| Field of View                         | 300°vertical <sup>6</sup> / 360° horizontal  |
| Step Size                             | 0.009 (40,960 3D-pixel on 360°) vertical / 0.0009 (40,960 3D-pixel on 360°) horizontal |
| Max. Scan Speed                       | 97Hz (vertical)  |
| Laser (Optical Transmitter)           |  |
| Laser Class                           | Laser Class 1  |
| Wavelength                            | 1550nm   |
| Beam Divergence                       | 0.3mrad (1/e)  |
| Beam Diameter at Exit                 | 2.12mm (1/e)   |
| Data Handling and Control             |  |
| Data Storage                          | SDHC™, SDXC™; 32GB; max. 512GB card  |
| Scanner Control                       | Via touch screen display and WLAN connection, Access by mobile devices with HTML5      |
| Interface Connection                  |  |
| WLAN                                  | 802.11n (150Mbit/s), as access point or client in existing networks                    |

| Additional Features                       |   |
|---|---|
| Dual Axis Compensator                     | Performs a leveling of each scan with an accuracy of 19 arcsec valid within ±2°                       |
| Height Sensor                             | Via an electronic barometer, the height relative to a fixed point can be detected and added to a scan |
| Compass <sup>7</sup>                      | The electronic compass gives the scan an orientation  |
| GNSS                                      | Integrated GPS & GLONASS  |
| On-Site Compensation*                     | Creates current quality report and improves compensation automatically                                |
| Accessory Bay*                            | The accessory bay connects versatile accessories to the scanner                                       |
| Inverse Mounting                          | Yes   |
| Real-time, On-site Registration in SCENE* | Connects to SCENE, real-time scan processing and registration, overview map                           |
| Electronic Automation Interface*          | Available as option, only at point of sale  |
| Digital Hash Function                     | Scans are cryptographically hashed and signed by the scanner  |
| Rescanning of Distant Targets             | Defined areas recaptured in higher resolution at a greater distance                                   |
| Retake Photos                             | Select individual photographs with unwanted objects and retake them                                   |

\*Not integrated with the Focus<sup>M</sup> 70

| General Specifications               |  |
|--------------------------------------|--|
| Power Supply                         | 19V (external supply), 14.4V (internal battery)  |
| Power Consumption                    | 15W idle, 25W scanning, 80W charging   |
| Battery Service Life                 | 4.5 hours  |
| Temperature                          | Operating: 5° - 40° C   Extended Operating <sup>8</sup> : -20° - 55° C   Storage: -10° - 60° C |
| Ingress Protection (IP) Rating Class | IP54   |
| Humidity Resistance                  | Non-condensing   |
| Weight                               | 4.2 kg (including battery)   |
| Size/Dimensions                      | 230 x 183 x 103mm  |
| Maintenance / Calibration            | Recommended annual   |



1. For a Lambertian scatterer. | 2. Ranging noise is defined as a standard deviation of values about the best-fit plane for measurement speed of 122,000 points/sec. | 3. Ranging error is defined as a systematic measurement error at around 10m and 25m. | 4. It is recommended to perform on-site compensation in the event the unit is exposed to exceptional temperature or mechanical stress. | 5. For distances larger 25m add 0.1mm/m of uncertainty. | 6. 2x150°, homogeneous point spacing is not guaranteed. | 7. Ferromagnetic objects can disturb the earth magnetic field and lead to inaccurate measurements. | 8. Low temperature operation: scanner has to be powered on while internal temperature is at or above 15°C, high temperature operation: additional accessory required.

All accuracy specifications are one sigma, after warm-up and within operating temperature range; unless otherwise noted. Subject to change without prior notice.

Local offices in over 25 countries around the world. Go to [www.faro.com](http://www.faro.com) to learn more.

**FARO Global Headquarters**  
250 Technology Park, Lake Mary, FL 32746, USA  
US: 800 736 0234 MX: +52 81 4170 3542  
BR: 11 3500 4600 / 0800 892 1192

**FARO Europe Regional Headquarters**  
Lingwiesenstr. 11/2  
70825 Korntal-Münchingen, Germany  
00 800 3276 7253

**FARO Asia Regional Headquarters**  
No. 3 Changi South Street 2, #01-01 Xilin  
Districentre Building B Singapore, 486548  
+65 65111350